

Safety Data Sheet

Section 1: Product and Company Identification

1.1 Product Identifiers:

Product Name: ABRAXIS® Microcystin HilR Standard

Product Code: 300654

1.2 Identified Use: Positive control for determination of Microcystin HilR in samples. **Restrictions on Use:** For research use only. **1.3 Company:** Gold Standard Diagnostics, 795 Horsham Road, Horsham, PA 19044 USA, info.abraxis@us.goldstandarddiagnostics.com

+1(215) 357-3911, FAX +1(215) 357-5232

1.4 Emergency Telephone Number: +1(215) 357-3911

Section 2: Hazard(s) Identification

2.1 Classification of the mixture:

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 2), H225 Highly flammable liquid and vapor

Acute toxicity, Oral (Category 2), H300 Fatal if swallowed; Acute toxicity, Oral (Category 3), H301 Toxic if swallowed

Acute toxicity, Inhalation (Category 1), H330 Fatal if inhaled; Acute toxicity, Inhalation (Category 3), H331 Toxic if inhaled

Acute toxicity, Dermal (Category 2), H310 Fatal in contact with skin; Acute toxicity, Dermal (Category 3), H311 Toxic in contact with skin

Skin irritation (Category 2), H315 Causes skin irritation

Eye irritation (Category 2A), H319 Causes serious eye irritation

Skin sensitization (Category 1), H317 May cause an allergic skin reaction

Specific target organ toxicity - single exposure (Category 3), H335 Respiratory system; Specific target organ toxicity - single exposure (Category

1), H370 Causes damage to organs

HMIS Rating: Health hazard: 2, Chronic Health Hazard: *, Flammability: 3, Physical Hazard 0

NFPA Rating: Health hazard: 2, Fire Hazard: 3, Reactivity Hazard: 0

2.2 GHS Label elements, including precautionary statements:

Pictogram(s)







Signal word: Danger Hazard statement(s):

H225 Highly flammable liquid and vapor.

H300 + H310 + H330 Fatal if swallowed, in contact with skin, or if inhaled

H301 + H311 + H331 Toxic if swallowed, in contact with skin, or if inhaled

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H370 Causes damage to organs.

Precautionary statement(s):

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

 ${\tt P241~Use~explosion-proof~electrical/ventilating/lighting~equipment}.$

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P260 Do not breathe dust/fume/ gas/ mist/vapors/spray.

P262 Do not get in eyes, on skin, or on clothing.

P264 Wash skin thoroughly after handling.

 $\ensuremath{\mathsf{P270}}$ Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/eye protection/face protection.

P284 Wear respiratory protection.

P301 + P310 + P330 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Rinse mouth.

P302 + P350 IF ON SKIN: Gently wash with plenty of soap and water.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304 + P340 + P311 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P307 + P311 If exposed: Call a POISON CENTER or doctor/physician.

 ${\tt P310\ Immediately\ call\ a\ POISON\ CENTER\ or\ doctor/physician}.$

P330 Rinse mouth.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

P337 + P313 If eye irritation persists: Get medical advice/attention.

P361 Remove/Take off immediately all contaminated clothing.

P362 Take off contaminated clothing and wash before reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

P403 + P233 + P235 Store in a well-ventilated place. Keep container tightly closed. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS: None known.

2.4 Unknown acute toxicity: None known.

Section 3: Composition / Information on Ingredients

3.1 Substances:

Name and Synonym(s): Microcystin HilR, MCY HilR Formula: C₅₀H₇₆N₁₀O₁₂

Molecular weight: 1009.2 g/mol CAS No.: No data available

Classification: Acute Toxicity 2, Acute Toxicity 1, Acute Toxicity 1; Skin Irritation 2; Eye Irritation 2; Skin Sensitization 1; STOT SE 3; H300 + H310

+ H330, H315, H319, H317, H335 Percentage in mixture: 0.000001 %

Hazardous component(s):

Name and Synonym(s): Methyl alcohol, MeOH, Methanol Formula: CH4O Molecular weight: 32.04 g/mol

CAS No.: 67-56-1 EC-No.: 200-659-6

Classification: Flammable Liquid 2, Acute Toxicity 3; STOT SE 1; H225, H301 + H311 + H331, H370

Percentage in Mixture: ~100 %

For full text of H-Statements mentioned in this Section, see Section 2.

Section 4: First Aid Measures

4.1 Description of first aid measures: Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area

If inhaled: If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact: Wash off with soap and plenty of water. Take victim immediately to hospital. Consult a physician.

In case of eye contact: Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

If swallowed: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed: The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed: No data available. Treat symptomatically.

Section 5: Fire-fighting Measures

5.1 Suitable extinguishing media: Dry powder or sand **Unsuitable extinguishing media:** Do NOT use water jet

5.2 Special hazards arising from the substance or mixture: Carbon oxides, nitrogen oxides

5.3 Advice for firefighters: Wear self-contained breathing apparatus for fire-fighting if necessary, and full protective gear to prevent contact with skin and eyes.

5.4 Further information: Use water spray to cool unopened containers.

Section 6: Accidental Release Measures

- **6.1 Personal precautions, protective equipment and emergency procedures:** Use personal protective equipment (see section 8). Avoid dust formation. Avoid breathing vapors, mist, dust, or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas.
- **6.2 Environmental precautions:** Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.
- **6.3** Methods and materials for containment and cleaning up: Contain spillage. Solids (if applicable): Pick up and arrange disposal without creating dust. Sweep up and shovel. Liquids (if applicable): Absorb with non-combustible liquid-binding material (sand, earth, diatomite, vermiculite). Keep in suitable, closed containers for disposal.

6.4 Reference to other sections: For information on safe handling see section 7.

For information on personal protection see section 8.

For information on disposal see section 13.

Section 7: Handling and Storage

7.1 Precautions for safe handling: See section 2. Avoid inhalation of vapors or mist, and avoid contact with skin and eyes. Wear appropriate personal protective equipment. Use explosion-proof equipment. Keep away from sources of ignition. Do not eat, drink, or smoke in work area. Take measures to prevent the buildup of electrostatic charge.

- **7.2 Precautions for safe storage:** Keep container(s) tightly closed in a dry, well-ventilated place. Protect from physical damage. Opened containers must be carefully resealed and kept upright to prevent leakage. See label or product insert for appropriate storage temperature and additional specific information. Storage class (TRGS 510): Flammable liquids.
- **7.3 Specific end use(s):** Other than use(s) specified in section 1, no other uses are stipulated.

Section 8: Exposure Controls / Personal Protection

8.1 Control parameters:

Component(s) with workplace control parameters

Methanol, CAS No. 67-56-1

Headache Nausea Nausea Nausea Dizziness Eye damage Substances for which there is a Biological Exposure Index or Indices (see BEI section) Danger of cutaneous absorption STEL 250.000000 ppm USA. ACGIH Threshold Limit Values (TLV)	Value	Control parameters	Basis
Nausea Dizziness Eye damage Substances for which there is a Biological Exposure Index or Indices (see BEI section) Danger of cutaneous absorption STEL 250.000000 ppm USA. ACGIH Threshold Limit Values (TLV) Headache Nausea Dizziness Eye damage Substances for which there is a Biological Exposure Index or Indices (see BEI section) Danger of cutaneous absorption TWA 200.000000 ppm; 260.000000 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200.000000 ppm; 325.000000 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200.000000 ppm; 260.000000 mg/m³ USA. NIOSH Recommended Exposure Limits The value in mg/m³ is approximate TWA 200 ppm; 260 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption ST 250 ppm; 325 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200 ppm; 260 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption ST 250 ppm; 325 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200 ppm; 260 mg/m³ USA. Occupational Exposure Limits; (OSHA) - Table Z-1 Limits for Air Contaminants The value in mg/m³ is approximate STEL 250 ppm; 325 mg/m³ USA. OSHA - TABLE Z-1 Limits for Air Contaminants USA. OSHA - TABLE Z-1 Limits for Air Contaminants USA. OSHA - TABLE Z-1 Limits for Air Contaminants USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000	TWA	200.000000 ppm	USA. ACGIH Threshold Limit Values (TLV)
Dizziness Eye damage Substances for which there is a Biological Exposure Index or Indices (see BEI section) Danger of cutaneous absorption STEL 250.000000 ppm USA. ACGIH Threshold Limit Values (TLV) Headache Nausea Dizziness Eye damage Substances for which there is a Biological Exposure Index or Indices (see BEI section) Danger of cutaneous absorption TWA 200.000000 ppm; 260.000000 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200.000000 ppm; 325.000000 mg/m³ USA. NIOSH Recommended Exposure Limits The value in mg/m³ is approximate TWA 200 ppm; 260 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200 ppm; 260 mg/m³ USA. NIOSH Recommended Exposure Limits; (OSHA) - Table Z-1 Limits for Air Contaminants Potential for dermal absorption TWA 200 ppm; 260 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200 ppm; 260 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200 ppm; 260 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200 ppm; 260 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200 ppm; 260 mg/m³ USA. Occupational Exposure Limits; (OSHA) - Table Z-1 Limits for Air Contaminants The value in mg/m³ is approximate STEL 250 ppm; 325 mg/m³ USA. OSCUpational Exposure Limits; (OSHA) - Table Z-1 Limits for Air Contaminants The value in mg/m³ is approximate STEL 250 ppm; 325 mg/m³ USA. OSCUPATIONALE Z-1 Limits for Air Contaminants - 1910.1000	Headache		
Eye damage Substances for which there is a Biological Exposure Index or Indices (see BEI section) Danger of cutaneous absorption STEL 250.000000 ppm USA. ACGIH Threshold Limit Values (TLV) Headache Nausea Dizziness Eye damage Substances for which there is a Biological Exposure Index or Indices (see BEI section) Danger of cutaneous absorption TWA 200.000000 ppm; 260.000000 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 250.000000 ppm; 325.000000 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200.000000 ppm; 260.000000 mg/m³ USA. NIOSH Recommended Exposure Limits The value in mg/m³ is approximate TWA 200 ppm; 260 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption ST 250 ppm; 325 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200 ppm; 260 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200 ppm; 260 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200 ppm; 260 mg/m³ USA. NIOSH Recommended Exposure Limits USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200 ppm; 260 mg/m³ USA. Occupational Exposure Limits; (OSHA) - Table Z-1 Limits for Air Contaminants The value in mg/m³ is approximate STEL 250 ppm; 325 mg/m³ USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000	Nausea		
Substances for which there is a Biological Exposure Index or Indices (see BEI section) Danger of cutaneous absorption STEL 250.000000 ppm USA. ACGIH Threshold Limit Values (TLV) Headache Nausea Dizziness Eye damage Substances for which there is a Biological Exposure Index or Indices (see BEI section) Danger of cutaneous absorption TWA 200.000000 ppm; 260.000000 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200.000000 ppm; 325.000000 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200.000000 ppm; 260.000000 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200 ppm; 260 mg/m³ USA. NIOSH Recommended Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants The value in mg/m³ is approximate TWA 200 ppm; 260 mg/m³ USA. NIOSH Recommended Exposure Limits USA. OCCUpational Exposure Limits; (OSHA) - Table Z-1 Limits for Air Contaminants The value in mg/m³ is approximate STEL 250 ppm; 325 mg/m³ USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000	Dizziness		
Index or Indices (see BEI section) Danger of cutaneous absorption STEL 250.000000 ppm USA. ACGIH Threshold Limit Values (TLV) Headache Nausea Dizziness Eye damage Substances for which there is a Biological Exposure Index or Indices (see BEI section) Danger of cutaneous absorption TWA 200.000000 ppm; 260.000000 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200.000000 ppm; 325.000000 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200.000000 ppm; 260.000000 mg/m³ USA. Occupational Exposure Limits; (OSHA) - Table 2-1 Limits for Air Contaminants The value in mg/m³ is approximate TWA 200 ppm; 260 mg/m³ USA. NIOSH Recommended Exposure Limits USA. NIOSH Recommended Exposure Limits USA. NIOSH Recommended Exposure Limits Limits USA. NIOSH Recommended Exposure Limits Limits USA. NIOSH Recommended Exposure Limits USA. NIOSH Recommended Exposure Limits USA. Occupational Exposure Limits; (OSHA) - Table 2-1 Limits for Air Contaminants The value in mg/m³ is approximate TWA 200 ppm; 260 mg/m³ USA. Occupational Exposure Limits; (OSHA) - Table 2-1 Limits for Air Contaminants The value in mg/m³ is approximate STEL 250 ppm; 325 mg/m³ USA. OSHA - TABLE 2-1 Limits for Air Contaminants - 1910.1000 USA. OSHA - TABLE 2-1 Limits for Air Contaminants - 1910.1000	Eye damage		
Danger of cutaneous absorption STEL 250.000000 ppm USA. ACGIH Threshold Limit Values (TLV) Headache Nausea Dizziness Eye damage Substances for which there is a Biological Exposure Index or Indices (see BEI section) Danger of cutaneous absorption TWA 200.000000 ppm; 260.000000 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200.000000 ppm; 325.000000 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200.000000 ppm; 260.000000 mg/m³ USA. NIOSH Recommended Exposure Limits The value in mg/m³ is approximate TWA 200 ppm; 260 mg/m³ USA. NIOSH Recommended Exposure Limits; (OSHA) - Table Z-1 Limits for Air Contaminants The value in mg/m³ is approximate TWA 200 ppm; 325 mg/m³ USA. NIOSH Recommended Exposure Limits USA. Occupational Exposure Limits; (OSHA) - Table Z-1 Limits for Air Contaminants The value in mg/m³ is approximate STEL 250 ppm; 325 mg/m³ USA. Occupational Exposure Limits; (OSHA) - Table Z-1 Limits for Air Contaminants The value in mg/m³ is approximate STEL 250 ppm; 325 mg/m³ USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000			
STEL Headache Nausea Dizziness Eye damage Substances for which there is a Biological Exposure Index or Indices (see BEI section) Danger of cutaneous absorption TWA 200.000000 ppm; 260.000000 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200.000000 ppm; 325.000000 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200.000000 ppm; 325.000000 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200.000000 ppm; 260.000000 mg/m³ USA. Occupational Exposure Limits; (OSHA) - Table Z-1 Limits for Air Contaminants The value in mg/m³ is approximate TWA 200 ppm; 260 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption ST 250 ppm; 325 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200 ppm; 260 mg/m³ USA. Occupational Exposure Limits; (OSHA) - Table Z-1 Limits for Air Contaminants The value in mg/m³ is approximate TWA 200 ppm; 260 mg/m³ USA. Occupational Exposure Limits; (OSHA) - Table Z-1 Limits for Air Contaminants The value in mg/m³ is approximate STEL 250 ppm; 325 mg/m³ USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation TWA 200 ppm; 260 mg/m³ USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000	· · · · · · · · · · · · · · · · · · ·		
Headache Nausea Dizziness Eye damage Substances for which there is a Biological Exposure Index or Indices (see BEI section) Danger of cutaneous absorption TWA 200.000000 ppm; 260.000000 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 250.000000 ppm; 325.000000 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200.000000 ppm; 260.000000 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200.000000 ppm; 260.000000 mg/m³ USA. Occupational Exposure Limits; (OSHA) - Table Z-1 Limits for Air Contaminants The value in mg/m³ is approximate TWA 200 ppm; 260 mg/m³ USA. NIOSH Recommended Exposure Limits USA. Occupational Exposure Limits; (OSHA) - Table Z-1 Limits for Air Contaminants The value in mg/m³ is approximate TWA 200 ppm; 260 mg/m³ USA. OSAA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation TWA 200 ppm; 260 mg/m³ USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000	·		
Nausea Dizziness Eye damage Substances for which there is a Biological Exposure Index or Indices (see BEI section) Danger of cutaneous absorption TWA 200.000000 ppm; 260.000000 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 250.000000 ppm; 325.000000 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200.000000 ppm; 260.000000 mg/m³ USA. Occupational Exposure Limits; (OSHA) - Table Z-1 Limits for Air Contaminants The value in mg/m³ is approximate TWA 200 ppm; 260 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption ST 250 ppm; 325 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200 ppm; 260 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200 ppm; 260 mg/m³ USA. Occupational Exposure Limits; (OSHA) - Table Z-1 Limits for Air Contaminants The value in mg/m³ is approximate STEL 250 ppm; 325 mg/m³ USA. Occupational Exposure Limits; (OSHA) - Table Z-1 Limits for Air Contaminants The value in mg/m³ is approximate STEL 250 ppm; 325 mg/m³ USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000	STEL	250.000000 ppm	USA. ACGIH Threshold Limit Values (TLV)
Dizziness Eye damage Substances for which there is a Biological Exposure Index or Indices (see BEI section) Danger of cutaneous absorption TWA 200.000000 ppm; 260.000000 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200.000000 ppm; 325.000000 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200.000000 ppm; 260.000000 mg/m³ USA. Occupational Exposure Limits; (OSHA) - Table Z-1 Limits for Air Contaminants The value in mg/m³ is approximate TWA 200 ppm; 260 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 250 ppm; 325 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200 ppm; 260 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200 ppm; 260 mg/m³ USA. Occupational Exposure Limits; (OSHA) - Table Z-1 Limits for Air Contaminants The value in mg/m³ is approximate STEL 250 ppm; 325 mg/m³ USA. Osha - Table Z-1 Limits for Air Contaminants - 1910.1000	Headache		
Eye damage Substances for which there is a Biological Exposure Index or Indices (see BEI section) Danger of cutaneous absorption TWA 200.000000 ppm; 260.000000 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 250.000000 ppm; 325.000000 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200.000000 ppm; 260.000000 mg/m³ USA. NIOSH Recommended Exposure Limits The value in mg/m³ is approximate TWA 200 ppm; 260 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption ST 250 ppm; 325 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200 ppm; 260 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200 ppm; 260 mg/m³ USA. Occupational Exposure Limits; (OSHA) - Table Z-1 Limits for Air Contaminants The value in mg/m³ is approximate STEL 250 ppm; 325 mg/m³ USA. Occupational Exposure Limits; (OSHA) - Table Z-1 Limits for Air Contaminants USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000	Nausea		
Substances for which there is a Biological Exposure Index or Indices (see BEI section) Danger of cutaneous absorption TWA 200.000000 ppm; 260.000000 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 250.000000 ppm; 325.000000 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200.000000 ppm; 260.000000 mg/m³ USA. Occupational Exposure Limits; (OSHA) - Table Z-1 Limits for Air Contaminants The value in mg/m³ is approximate TWA 200 ppm; 260 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption ST 250 ppm; 325 mg/m³ USA. NIOSH Recommended Exposure Limits USA. Occupational Exposure Limits for Air Contaminants The value in mg/m³ is approximate STEL 250 ppm; 325 mg/m³ USA. Occupational Exposure Limits; (OSHA) - Table Z-1 Limits for Air Contaminants USA. OSHA - TABLE Z-1 Limits for Air Contaminants USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000	Dizziness		
Index or Indices (see BEI section) Danger of cutaneous absorption TWA 200.000000 ppm; 260.000000 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 250.000000 ppm; 325.000000 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200.000000 ppm; 260.000000 mg/m³ USA. Occupational Exposure Limits; (OSHA) - Table Z-1 Limits for Air Contaminants The value in mg/m³ is approximate TWA 200 ppm; 260 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption ST 250 ppm; 325 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200 ppm; 260 mg/m³ USA. NIOSH Recommended Exposure Limits USA. NIOSH Recommended Exposure Limits USA. Occupational Exposure Limits; (OSHA) - Table Z-1 Limits for Air Contaminants The value in mg/m³ is approximate STEL 250 ppm; 325 mg/m³ USA. OCCUpational Exposure Limits; (OSHA) - Table Z-1 Limits for Air Contaminants USA. OSHA - TABLE Z-1 Limits for Air Contaminants USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000	, ,		
Danger of cutaneous absorption TWA 200.000000 ppm; 260.000000 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 250.000000 ppm; 325.000000 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200.000000 ppm; 260.000000 mg/m³ USA. NIOSH Recommended Exposure Limits USA. Occupational Exposure Limits; (OSHA) - Table Z-1 Limits for Air Contaminants The value in mg/m³ is approximate TWA 200 ppm; 260 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption ST 250 ppm; 325 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200 ppm; 260 mg/m³ USA. Occupational Exposure Limits; (OSHA) - Table Z-1 Limits for Air Contaminants The value in mg/m³ is approximate STEL 250 ppm; 325 mg/m³ USA. Occupational Exposure Limits; (OSHA) - Table Z-1 Limits for Air Contaminants USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation TWA 200 ppm; 260 mg/m³ USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000			
TWA 200.000000 ppm; 260.000000 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption ST 250.000000 ppm; 325.000000 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200.000000 ppm; 260.000000 mg/m³ USA. Occupational Exposure Limits; (OSHA) - Table Z-1 Limits for Air Contaminants The value in mg/m³ is approximate TWA 200 ppm; 260 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption ST 250 ppm; 325 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200 ppm; 260 mg/m³ USA. Occupational Exposure Limits; (OSHA) - Table Z-1 Limits for Air Contaminants The value in mg/m³ is approximate STEL 250 ppm; 325 mg/m³ USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation TWA 200 ppm; 260 mg/m³ USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000	· · · · · · · · · · · · · · · · · · ·		
Potential for dermal absorption ST 250.000000 ppm; 325.000000 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200.000000 ppm; 260.000000 mg/m³ USA. Occupational Exposure Limits; (OSHA) - Table Z-1 Limits for Air Contaminants The value in mg/m³ is approximate TWA 200 ppm; 260 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption ST 250 ppm; 325 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200 ppm; 260 mg/m³ USA. Occupational Exposure Limits; (OSHA) - Table Z-1 Limits for Air Contaminants The value in mg/m³ is approximate STEL 250 ppm; 325 mg/m³ USA. Occupational Exposure Limits; (OSHA) - Table Z-1 Limits for Air Contaminants The value in mg/m³ is approximate STEL 250 ppm; 325 mg/m³ USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation TWA 200 ppm; 260 mg/m³ USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000			
ST 250.000000 ppm; 325.000000 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200.000000 ppm; 260.000000 mg/m³ USA. Occupational Exposure Limits; (OSHA) - Table Z-1 Limits for Air Contaminants The value in mg/m³ is approximate TWA 200 ppm; 260 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption ST 250 ppm; 325 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200 ppm; 260 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200 ppm; 260 mg/m³ USA. Occupational Exposure Limits; (OSHA) - Table Z-1 Limits for Air Contaminants The value in mg/m³ is approximate STEL 250 ppm; 325 mg/m³ USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation TWA 200 ppm; 260 mg/m³ USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000	TWA	200.000000 ppm; 260.000000 mg/m ³	•
Limits Potential for dermal absorption TWA 200.000000 ppm; 260.000000 mg/m³ USA. Occupational Exposure Limits; (OSHA) - Table Z-1 Limits for Air Contaminants The value in mg/m³ is approximate TWA 200 ppm; 260 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption ST 250 ppm; 325 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200 ppm; 260 mg/m³ USA. Occupational Exposure Limits; (OSHA) - Table Z-1 Limits for Air Contaminants The value in mg/m³ is approximate STEL 250 ppm; 325 mg/m³ USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation TWA 200 ppm; 260 mg/m³ USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000	Potential for dermal absorption		
TWA 200.000000 ppm; 260.000000 mg/m³ USA. Occupational Exposure Limits; (OSHA) - Table Z-1 Limits for Air Contaminants The value in mg/m³ is approximate TWA 200 ppm; 260 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption ST 250 ppm; 325 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200 ppm; 260 mg/m³ USA. Occupational Exposure Limits; (OSHA) - Table Z-1 Limits for Air Contaminants The value in mg/m³ is approximate STEL 250 ppm; 325 mg/m³ USA. OCCUpational Exposure Limits; (OSHA) - Table Z-1 Limits for Air Contaminants USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation TWA 200 ppm; 260 mg/m³ USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000	ST	250.000000 ppm; 325.000000 mg/m ³	•
The value in mg/m³ is approximate TWA 200 ppm; 260 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption ST 250 ppm; 325 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200 ppm; 260 mg/m³ USA. Occupational Exposure Limits; (OSHA) - Table Z-1 Limits for Air Contaminants The value in mg/m³ is approximate STEL 250 ppm; 325 mg/m³ USA. OSHA - TABLE Z-1 Limits for Air Contaminants USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation TWA 200 ppm; 260 mg/m³ USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000	Potential for dermal absorption		
TWA 200 ppm; 260 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption ST 250 ppm; 325 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200 ppm; 260 mg/m³ USA. Occupational Exposure Limits; (OSHA) - Table Z-1 Limits for Air Contaminants The value in mg/m³ is approximate STEL 250 ppm; 325 mg/m³ USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation TWA 200 ppm; 260 mg/m³ USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000	TWA	200.000000 ppm; 260.000000 mg/m ³	USA. Occupational Exposure Limits; (OSHA) - Table Z-1 Limits for Air Contaminants
Limits Potential for dermal absorption ST	The value in mg/m³ is approximate		
ST 250 ppm; 325 mg/m³ USA. NIOSH Recommended Exposure Limits Potential for dermal absorption TWA 200 ppm; 260 mg/m³ USA. Occupational Exposure Limits; (OSHA) - Table Z-1 Limits for Air Contaminants The value in mg/m³ is approximate STEL 250 ppm; 325 mg/m³ USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation TWA 200 ppm; 260 mg/m³ USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000	TWA	200 ppm; 260 mg/m ³	·
Potential for dermal absorption TWA 200 ppm; 260 mg/m³ USA. Occupational Exposure Limits; (OSHA) - Table Z-1 Limits for Air Contaminants The value in mg/m³ is approximate STEL 250 ppm; 325 mg/m³ USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation TWA 200 ppm; 260 mg/m³ USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000	Potential for dermal absorption		
TWA 200 ppm; 260 mg/m³ USA. Occupational Exposure Limits; (OSHA) - Table Z-1 Limits for Air Contaminants The value in mg/m³ is approximate STEL 250 ppm; 325 mg/m³ USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation TWA 200 ppm; 260 mg/m³ USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000	ST	250 ppm; 325 mg/m ³	•
- Table Z-1 Limits for Air Contaminants The value in mg/m³ is approximate STEL 250 ppm; 325 mg/m³ USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation TWA 200 ppm; 260 mg/m³ USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000	Potential for dermal absorption		
STEL 250 ppm; 325 mg/m³ USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 Skin notation TWA 200 ppm; 260 mg/m³ USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000	TWA	200 ppm; 260 mg/m ³	USA. Occupational Exposure Limits; (OSHA) - Table Z-1 Limits for Air Contaminants
Contaminants - 1910.1000 Skin notation TWA 200 ppm; 260 mg/m³ USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000	The value in mg/m³ is approximate		
TWA 200 ppm; 260 mg/m³ USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000	5 5 5	250 ppm; 325 mg/m ³	
Contaminants - 1910.1000	Skin notation		
	TWA	200 ppm; 260 mg/m ³	
Skin notation	Skin notation		

Biological occupational exposure limits

Methanol, CAS No. 67-56-1

Parameters	Value	Biological specimen	Basis
Methanol	15.0000 mg/l	Urine	ACGIH – Biological Exposure
			Indices (BEI)
End of shift (As soon as possible after exposure ceases)			

Derived No Effect Level (DNEL)

Methanol, CAS No. 67-56-1

Wictilation, CAS NO. 07 SO 1			
Application area	Exposure routes	Health effect	Value
Workers	Skin contact	Long-term systemic effects, Acute systemic effects	40mg/kg BW/d
Consumers	Skin contact	Long-term systemic effects, Acute systemic effects	8mg/kg BW/d
Consumers	Ingestion	Long-term systemic effects, Acute systemic effects	8mg/kg BW/d

Workers	Inhalation	Acute systemic effects, Acute local effects, Long-term 260 mg/m ³	
		systemic effects, Long-term local effects	
Consumers	Inhalation	Acute systemic effects, Acute local effects, Long-term	50 mg/m ³
		systemic effects, Long-term local effects	

Predicted No Effect Concentration (PNEC)

Methanol, CAS No. 67-56-1

Compartment	Value
Soil	23.5 mg/kg
Marine water	15.4 mg/l
Fresh water	154 mg/l
Fresh water sediment	570.4 mg/kg
Onsite sewage treatment plant	100 mg/kg

8.2 Exposure controls:

Appropriate engineering controls: Provide adequate ventilation. Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. Keep away from food and beverages.

Personal protective equipment

Eye protection: Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166 (EU).

Skin protection: Handle with chemical resistant gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Respiratory protection: Use a chemical fume hood or approved respiratory protection equipment.

Body protection: Lightweight, protective clothing to prevent skin exposure.

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

Section 9: Physical and Chemical Properties

9.1 Information on basic physical and chemical properties of mixture

Appearance: Liquid Odor: No data available Odor Threshold: No data available

pH: No data available Melting point/freezing point: No data available

Initial boiling point and boiling range: No data available Flash point: No data available

Evaporation rate: No data available **Flammability (solid, gas):** No data available

Upper/lower flammability or explosive limits No data available Vapor pressure: No data available

Vapor density: No data available Relative density: No data available

Water solubility: No data available Partition coefficient: n-octanol/water: No data available

Auto-ignition temperature: Not applicable Decomposition temperature: No data available

Viscosity: No data available Explosive properties: No data available Oxidizing properties: No data available

9.2 Other information: No data available

Section 10: Stability and Reactivity

10.1 Reactivity: No data available

10.2 Chemical stability: Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions: No data available

10.4 Conditions to avoid: Keep away from open flame, hot surfaces, heat sources, and sources of ignition.

10.5 Incompatible materials: Acid chlorides, acid anhydrides, strong oxidizing agents, alkali metals, reducing agents, acids, peroxides

10.6 Hazardous decomposition products: No data available. In the event of fire: see section 5.

Section 11: Toxicological Information

11.1 Information on toxicological effects

To the best of our knowledge, the chemical, physical, and toxicological properties of this product have not been thoroughly investigated. **Acute toxicity** (Microcystin HilR):

InhalationNo data availableIngestionNo data availableSkin contactIrritant to skin and mucous membranesEye contactIrritating effectRespiratory or skin sensitizationSensitization possible through skin contact

Aspiration hazard No data available

Acute toxicity (Methanol, CAS No. 67-56-1):

Inhalation LC50 Inhalation - Rat - 4 h - 128.2 mg/l; LC50 Inhalation - Rat - 6 h - 87.6 mg/l; LD50 Dermal - Rabbit - 17,100 mg/kg Ingestion LDLO Oral - Human - 143 mg/kg (Lungs, Thorax, or Respiration: Dyspnea. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea); LD50 Oral - Rat - 1,187 - 2,769 mg/kg

Skin contact Rabbit skin—no irritation **Eye contact** Rabbit eye—no irritation

Respiratory or skin sensitization Maximization Test (GPMT)(OECD Test Guideline 406)--Guinea pig--does not cause skin sensitization **Aspiration hazard** No data available

Mutagenicity (Methanol, CAS No. 67-56-1): Ames test (*S. typhimurium*)--Result: negative; *in vitro* assay (fibroblasts)--Result: negative; *in vivo* mammalian bone-marrow cytogenetic test, chromosomal analysis (mouse, male and female)--Result: negative

Carcinogenicity:

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP. OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Teratogenicity: No data available Reproductive/fertility toxicity: Damage to fetus not classifiable

Specific target organ toxicity, single exposure: Inhalation—may cause respiratory irritation

Specific target organ toxicity, repeated exposure: No data available

Additional information: (Microcystin HilR): Danger through skin adsorption. (Methanol, CAS No. 67-56-1): RTECS: PC1400000 Effects due to ingestion may include headache, dizziness, drowsiness, metabolic acidosis, coma, seizures. Methanol may be fatal or cause blindness if swallowed. Stomach - Irregularities - Based on Human Evidence

Section 12: Ecological Information

12.1 Toxicity: No data available

12.2 Persistence and degradability: No data available **12.3 Bioaccumulative potential:** No data available

12.4 Mobility in soil: No data available

12.5 Results of PBT and vPvB assessment: No data available

12.6 Other adverse effects: Do not allow product to reach ground water, water bodies or sewage system, even in small quantities.

Section 13: Disposal Considerations

13.1 Waste treatment methods

Product: All waste must be handled and disposed according to local, state, and federal regulations. Avoid disposing large volumes in sewer. **Contaminated packaging:** All waste must be handled and disposed according to local, state, and federal regulations. Refer to sections 7 and 8 for safe handling guidance.

Section 14: Transport Information

 ${\tt DOT, Land\ Transport\ ADR/RID\ (cross-border),\ Maritime\ Transport\ IMDG,\ Air\ Transport\ ICAO-TI\ and\ IATA-DGR}$

UN Number: 3316

UN Proper shipping name: Chemical Kit, (contains Methanol)

Transport hazard class(es): 9

Packing group: III

Environmental hazard: See section 12
Bulk transport: Excepted/Limited quantity
Special considerations: See section 7 for handling

Section 15: Regulatory Information

EU Regulations, Hazard Symbol(s): Methanol: T (Toxic), F (Flammable)

Safety Phrases: Methanol: S 7 / 16 / 36 / 37 / 45, Keep container tightly closed. Keep away from sources of ignition, no smoking. Wear suitable protective clothing and gloves. In case of accident or if you become ill, seek medical advice immediately (show product label).

SARA Title III, Section 302 Components: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA Title III, Section 313 Components: Methanol, CAS No. 67-56-1

SARA 311/312 Hazards: Methanol, CAS No. 67-56-1: Fire Hazard, Acute Health Hazard, Chronic Health Hazard

State Right-to-Know

Massachusetts: Methanol, CAS No. 67-56-1 Pennsylvania: Methanol, CAS No. 67-56-1 New Jersey: Methanol, CAS No. 67-56-1

California Prop. 65 Components: WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm. Methanol, CAS No. 67-56-1

Section 16: Other information

This information is based on our present knowledge. While Gold Standard Diagnostics believes that the data contained herein are factual and the opinions expressed represent a best effort to present accurate information, the data are not to be taken as a warranty or representation for which Gold Standard Diagnostics assumes legal responsibility. The information shall not be taken as being all-inclusive and is to be used only as a guide. The data are offered solely for the user's consideration, investigation, and verification. These suggestions should not be confused with either state, municipal, or insurance requirements, or with national safety codes and constitute no warranty. Any use of these data and information must be determined by the user to be in accordance with applicable federal, state, and local regulations.

All materials and mixtures may present unknown hazards and should be used with caution. Since Gold Standard Diagnostics cannot control the methods, volumes, or conditions of use of this product, Gold Standard Diagnostics shall not be held liable for any damages or losses resulting from the handling or from contact with the product as described herein. An individual technically qualified to handle potentially hazardous chemicals must supervise the use of this material. This product is sold for research use only. It is not for any human or animal therapeutic or clinical diagnostic use.

Date this SDS is effective: 05/16/2024

Version: 01